TEAC®



SERVICE MANUAL

A-70/A-50

DC Integrated Stereo Amplifier

5704010900

1 SPECIFICATIONS

Type DC Integrated Stereo Amplifier

Rated Output Power
50 W + 50 W (A-50: 30 W + 30 W),
Both Channels, 8 ohms 30 Hz – 20 kHz,
0.05% (A-50: 0.06%) T.H.D.

Total Harmonic Distortion
1 kHz, at Rated Output Power, 0.006%
(A-50: 0.01%)

Output Bandwidth
IHF, -3 dB, 10 Hz – 50 kHz

Frequency Response
Tuner/Aux/Tape 1, 2 to SP out
10 Hz – 55 kHz +0, -2 dB
Phono to Rec Out, 20 Hz – 20 kHz ± 0.5 dB
(RIAA)

Input Sensitivity
Phono MC 200 μV/100 ohms (A-70 only)
Phono MM 2.5 mV/47 k ohms
Tuner/Aux/Tape 1, 2 150 mV/33 k ohms

Rated Output Voltage/Impedance
Tape Rec 1, 2 150 mV/33 k ohms

Signal-to-Noise Ratio (IHF A Network)
Phono MC 66 dB (A-70 only)
Phono MM 82 dB
Tuner/Aux/Tape 1, 2 96 dB

Damping Factor 30

Tone Control
Bass ±10 dB, 100 Hz
Treble ±10dB, 10 kHz

High Filter 10 kHz, 6 dB/oct

Subsonic Filter 15 Hz, 6 dB/oct

Muting 20 dB

Power Requirements
100/120/220/240 V AC 50/60 Hz,
92 W (A-50: 52 W) (General Export Model)
120 V AC 60 Hz, 98 W (A-50: 60 W)
(U.S.A. Model)
120 V AC 60 Hz, 1.7 A (A-50: 1.4 A)
(Canada Model)
220 V AC 50 Hz, 270 W (A-50: 160 W)
(Europe Model)
240 V AC 50 Hz, 350 W (A-50: 190 W)
(U.K./Aus. Model)

Dimensions (W x H x D)
432 x 72 x 296 mm (17" x 2-13/16" x 11-5/8")

Weight 7 kg (15-7/16 lbs) net

- Improvements may result in specification or feature changes without notice.
- Photos may differ slightly from production models.

NOTES

1. **In this manual, 0 dB is referenced to 1 V.**
2. ⚠ Parts marked with this sign are safety critical components. They must always be replaced with identical components – refer to the appropriate parts list and ensure exact replacements.
3. PC boards shown are viewed from foil side.

2 VOLTAGE CONVERSION
(FOR GENERAL EXPORT MODELS)

BE SURE TO REMOVE THE POWER CORD FROM THE AC OUTLET BEFORE REMOVING THE METAL COVER AND REPOSITIONING THE VOLTAGE CONVERSION PLUG.

1. Remove the metal housing covering the top and sides of the unit by removing the screws from each side of the metal cover.
2. Locate the voltage selector plug on the left side of the unit.
3. Remove the plug by pulling it out, then re-insert it so that the arrow on the plug is aligned with the white line indicating the proper voltage.
4. Replace the cover.



Fig. 2-1

3 PARTS AND ADJUSTMENTS LOCATION



Fig. 3-1

4 ADJUSTMENTS

4-1 INITIAL SETTINGS

Without applying AC power, set the controls as shown below.

Control	Position or setting
SPEAKERS	A
BASS	0
TREBLE	0
Input	AUX
TAPE COPY	OUT
MONITOR	SOURCE
MUTING	OUT

Control	Position or setting
FILTER	OUT
LOUDNESS	OUT
MODE	STEREO
BALANCE	Center
VOLUME	min
CARTRIDGE	MM (A-70 only)

4-2 DC BALANCE CHECK

1. Connect the DC voltmeter to SPEAKERS A terminal.
2. Depress POWER switch to ON.
3. Confirm the DC voltmeter indication within 0 V ±50 mV.
4. If the DC voltmeter indicates over +50 mV, cut the orange cable between 3 and 3 terminals (for L-ch) or the yellow cable between 4 and 4 terminals (for R-ch) on the MAIN PCB.
5. If the DC voltmeter indicates less than −50 mV, cut the brown cable between 1 and 1 terminals (for L-ch) or the red cable between 2 and 2 terminals (for R-ch) on the MAIN PCB.

4-3 IDLING CURRENT CHECK

1. Connect the DC voltmeter between TP-3 (L-ch)/TP-5 (R-ch) and TP-1 (L-ch)/TP-6 (R-ch) for the A-70 or TP-2 (L-ch)/TP-5 (R-ch) and TP-1 (L-ch)/TP-4 (R-ch) for the A-50.
2. Confirm the DC voltmeter indication within 5 mV when POWER is ON after 10 seconds.
3. If the DC voltmeter indicates over 5 mV (A-70) or 7 mV (A-50), cut the blue cable between 6 and 6 terminals for LEFT channel or the violet cable between 7 and 7 terminals for RIGHT channel on the MAIN PCB.
4. After the above procedures, allow 10 minites for the amplifier to warm up completely.
5. Confirm the DC voltmeter indication which should be within 2 to 25 mV.

4-4 PEAK LEVEL DISPLAY ADJUSTMENT

1. Connect the AC voltmeter to SPEAKERS A terminal.
2. Set the VOLUME control to maximum.
3. Apply a 1 kHz input signal to provide an output voltage of 25 V (A-70) or 20 V (A-50) to the AUX terminal.
4. Adjust VR4 on the DISPLAY PCB so that the 50 W (A-70) or 30 W (A-50) LED in the PEAK LEVEL DISPLAY lights up with the full intensity but the 100W (A-70) or 60 W (A-50) LED do not light.



Fig. 4-1

4-5 RELAY OPERATION CHECK (A-70)

1. Apply 1 kHz/150 mV (−16.5 dB) to the AUX terminal.
2. Adjust the VOLUME control so that output voltage is 1 V at the SPEAKER terminal.
3. Apply a +2.5 V or −2.5 V DC to the TP-7 to couse the relay RY1 to break immediately.
4. Remove the DC signal from the TP-7.
5. Adjust the VOLUME control so that output voltage is 0.5 V at the SPEAKER terminal.
6. Shortcircuit the SPEAKER terminal between + and − so that the relay RY1 break immediately.

5 BLOCK DIAGRAM



Fig. 5-1

6 PARTS LOCATION AND PARTS LIST

PARTS LOCATION-1



Parts marked with *require longer deliver time.

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
1 - 1		Sheet, Escutcheon	Part of 1 - 4
1 - 2	*5760108100	Cover, Top	
1 - 3	*5760094400	Button, Push; C	
1 - 4	*5760219300	Panel Assy, Front	A-70
	*5760219200	Panel Assy, Front	A-50
1 - 5	*5760094100	Button, Push; A	
1 - 6	*5760108000	Knob, BALANCE	
1 - 7	*5760107900	Knob, VOLUME	
1 - 8	*5783114006	Screw, M4x6 (BLK)	
1 - 9	*5760094300	Button, Push; B	
1 - 10		Plate, Scale	A-70 Part of 1 - 4
		Plate, Scale	A-50 Part of 1 - 4
1 - 11		Plate, Meter	Part of 1 - 4
1 - 12	*5760107800	Knob, Tone	
1 - 13	*5760094000	Button, POWER	

INCLUDED ACCESSORIES

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
	5700021500	Owner's Manual	

PARTS LOCATION-2



Parts marked with *require longer delivery time.

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
2 - 1	*5760142100	Jack, Pin; 2P	
2 - 2	*5330505200	Jack, Pin; 6P	
2 - 3	*5760103500	Panel, Rear; A [US, C, GE]	
	*5760107300	Panel, Rear; B [E, UK, A]	
2 - 4	*5760102700	Terminal, Push; 8P	
2 - 5	⚠*5760101000	Socket, AC; 3P [US, GE]	
	⚠*5760098600	Socket, AC; 3P [C]	
2 - 6	*5800136400	Strain Relief, Cord; 4P-4 [US, C, GE]	
	*5800136500	Strain Relief, Cord; 4K-4 [E, UK, A]	
2 - 7	⚠*5760098100	Cord, AC Power [US, C, GE]	
	⚠*5760098200	Cord, AC Power [E]	
	⚠*5760098300	Cord, AC Power [UK]	
	⚠*5760098400	Cord, AC Power [A]	
2 - 8	*5760081300	Nut, GND	
	*5785213000	Washer, Fiber (BLK) ϕ3 x ϕ6 x t0.5	

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

PARTS LOCATION-3



Parts marked with *require longer delivery time.

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
3 - 1	*5760108300	Cover, Bottom	
3 - 2	*5760095000	Foot	
3 - 3	*5783114006	Screw, M4x6 (BLK)	

PARTS LOCATION-4



Parts marked with *require longer delivery time.

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
4 - 1	*5760219300	Panel Assy, Front	A-70
	*5760219200	Panel Assy, Front	A-50
4 - 2	*5760095500	Cushion, A	
4 - 3		Guide, Button; B	Part of 4 - 1
4 - 4	*5760109600	PCB, LED Assy	
		Escutcheon, Panel	Part of 4 - 1
4 - 5			
4 - 6	*5760109900	PCB Assy, DISPLAY [All except C]	
	*5760109910	PCB Assy, DISPLAY [C]	
4 - 7		Guide, Button; A	Part of 4 - 1
4 - 8		Cover, Knob	Part of 4 - 1

PARTS LOCATION-5



Parts marked with *require longer delivery time.

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
5 - 1	*5760101300	Flame, Front	
5 - 2	*5760101400	Flame, Front	
5 - 3	5760121200	Var. Res., 250kΩ(B)x2/500kΩ(W)	
5 - 4	*5760141300	Jack, Headphone	
5 - 5	*5760108400	Bracket, Jack	

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

PARTS LOCATION-6



Parts marked with *require longer delivery time.

REF. NO.	PARTS NO.	DESCRIPTION	REMARKS
6 - 1	*5760095600	Cushion, B	
6 - 2	*5760109400	PCB Assy, SP TERMINAL [All except C]	
	*5760109410	PCB Assy, SP TERMINAL [C]	
6 - 3	*5760109200	PCB Assy, MAIN [US]	A-70
	*5760109210	PCB Assy, MAIN [C]	A-70
	*5760109220	PCB Assy, MAIN [All except US, C]	A-70
	*5760110400	PCB Assy, MAIN [US]	A-50
	*5760110410	PCB Assy, MAIN [C]	A-50
	*5760110420	PCB Assy, MAIN [All except US, C]	A-50
6 - 4	*5760092600	Frame, Side	
6 - 5	*5760108800	Bracket, Heatsink; R	
6 - 6	*5760109700	PCB Assy, PUSH SW-A [All except C]	A-70
	*5760109710	PCB Assy, PUSH SW-A [C]	A-70
	*5760110600	PCB Assy, PUSH SW-A [All except C]	A-50
	*5760110610	PCB Assy, PUSH SW-A [C]	A-50
6 - 7	*5760109800	PCB Assy, PUSH SW-B·C [All except C]	
	*5760109810	PCB Assy, PUSH SW-B·C [C]	
6 - 8	*5760121500	Heatsink, B	A-70
	*5760121400	Heatsink, A	A-50
6 - 9	*5760108700	Bracket, Heatsink; L	
6 - 10	⚠*5332011200	Socket, Voltage Selector [GE]	
6 - 11	⚠*5133014000	Plug, Voltage Selector [GE]	
6 - 12	*5760108500	Bracket, VR	
6 - 13	*5760109300	PCB Assy, SELECTOR SW [All except C]	
	*5760109310	PCB Assy, SELECTOR SW [C]	
6 - 14	*5760109500	PCB Assy, HEADPHON JACK [All except C]	
	*5760109510	PCB Assy, HEADPHON JACK [C]	
6 - 15	5760093900	Rod, Power Switch	
6 - 16	⚠ 5760117900	Switch, Power [US, C]	
	⚠*5760118000	Switch, Power [All except US, C]	
6 - 17	⚠*5760099900	Spark Killer [US, C]	
	⚠*5267703100	Spark Killer [All except US, C]	
6 - 18	⚠*5760117000	Transformer, Power [US, C]	A-70
	⚠*5760117100	Transformer, Power [GE]	A-70
	⚠*5760117200	Transformer, Power [E]	A-70
	⚠*5760117300	Transformer, Power [UK, A]	A-70
	⚠*5760117500	Transformer, Power [US, C]	A-50
	⚠*5760117600	Transformer, Power [GE]	A-50
	⚠*5760117700	Transformer, Power [E]	A-50
	⚠*5760117800	Transformer, Power [UK, A]	A-50
6 - 19	*5760108200	Bracket, Transformer	

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

ASSEMBLING HARDWARE CODING LIST

All screws conform to ISO standards, and have crossrecessed heads, unless otherwise noted. ISO screws have the head inscribed with a point as in the figure to the right.



FOR EXAMPLE:

B M 3 x 6

- B — Nomenclature
- M — Metric System
- 3 — Diameter in mm (D) *
- 6 — Length in mm (L)



* Inner dia. for washers and nuts

	Code	Name	Type
MACHINE SCREW	R	Round Head Screw	
	P	Pan Head Screw	
	T	Stove Head Screw (Truss)	
	B	Binding Head Screw	
	F	Flat Countersunk Head Screw	
	O	Oval Countersunk Head Screw	
WOOD SCREW	RW	Round Head Wood Screw	
TAPTITE SCREW	PTT	Pan Head Taptite Screw	
	WTT	Washer Head Taptite Screw	
SEMS SCREW	BSA	Binding Head SEMS Screw(A Type)	
	BSB	Binding Head SEMS Screw(B Type)	
	BSF	Binding Head SEMS Screw(F Type)	
	PSA	Pan Head SEMS Screw(A Type)	
	PSB	Pan Head SEMS Screw(B Type)	

	Code	Name	Type
TAPPING SCREW	BTA	Binding Head Tapping Screw(A Type)	
	BTB	Binding Head Tapping Screw(B Type)	
	RTA	Round Head Tapping Screw(A Type)	
	RTB	Round Head Tapping Screw(B Type)	
SETSCREW	SF	Hex Socket Setscrew(Flat Point)	
	SC	Hex Socket Setscrew(Cup Point)	
	SS	Slotted Socket Setscrew(Flat Point)	
WASHER	E	E-Ring (Retaining Washer)	
	W	Flat Washer (Plain)	
	SW	Lock Washer (Spring)	
	LWI	Lock Washer (Internal Teeth)	
	LWE	Lock Washer (External Teeth)	
	TW	Trim Washer (Countersunk)	
NUT	N	Hex Nut	

7 PC BOARDS AND PARTS LIST

PC Boards shown viewed from foil side.

MAIN PCB ASSY (A-70)


C1 0.047
R102 47k
R103 22
C101 0.001
R101 100
R108 120
R109 10
C104 470p
C102 68p
C103 68p
C204 470p
R207 4.7k
C205 2200/10V
R105 4.7k
R104 4.7k
C103 0.001
R106 390
R110 68k
R111 5.6k
C107 0.01
C106 0.047
R112 5.6k
C108 0.0033
R113 120
R114 560
C110 0.0047
R115 330k
C109 3.3/50V
R202 47k
R203 22
C201 0.001
R201 100
R208 120
R209 10
R205 4.7k
R204 4.7k
R206 390
C203 0.001
R210 68k
R211 5.6k
C206 0.047
C207 0.01
R212 5.6k
C208 0.0033
C209 3.3/50V
R213 120
R214 560
C210 0.0047
R215 330k
IC101
Q101
Q201
Q102
Q202
C211 33/25V
R7 12k
R6 1.2k
R5 1.2k
C4 0.01
R4 330
R8 330
C5 47p
C6 0.01
C7 33/10V
C10 47p
R3 5.6k
D1 052-5.6V
R2 8.2k
R1 820
C2 0.01
Q1
Q2
Q3
Q4
Q5
Q6
TP9
TP8
L
SI
R
C3 100/25V
C8 100/25V
R22 3.3k
Q212
TP4
TP5
TP6
R247 0.33(5W)x2
R11 100
C16 220/50V
C23 0.01
C24 10/35V
C25 47/50V
D6 052-13U
R24 470
R23 100(3W)
R25 2.7k(1/2W)
R26 68k
R27 22k
C18 47/63V
C20 4.7/50V
R35 10/25V
R28 5.6k
D7 052-5.1U
R20 3.9k
R14 47k
D3 1S1555
R16 560k
Q7
R17 68k
R18 6.8k
R12 4.7k
R13 6.8k
D2 1S1555
R15 3.3k
D1 1S1555
R28 5.6k
C201 220/16V (BP)
R248 2.2k
Q214
C27 4700/53V
C26 4700/53V
C233 0.047
R249 4.7k
R250 10(1W)
C234 0.047
R251 4.7k
R150 10(1W)
C134 0.047
R50 3.3k(1W)
R51 3.3k(1W)
C22 0.01/1.4kV
C28 0.01/1.4kV
F2 F5.0A 250V
F1 F5.0A 250V
BLK
YEL
D10 U05C
D9 U05C
D12 U05C
D11 U05C
TP2
TP1
TP3
R147 0.33(5W)x2
Q113
RY1
L201
R252 6.8(1W)
R152 6.8(1W)
L101
D4 052-20U
D5 052-20U
R21 820(1W)
R19 820(1W)
D8 1S1555
D9 1S1555
D10 1S1555
R18 18k
R17 5.6k
R16 10k
R15 2.2k
R14 1.5k
R13 4.7k
R12 6.8k
R11 4.7k
R10 6.8k
R9 3.9k
Q8
Q9
Q10
Q11
S527
S527
S527

MAIN PCB ASSY (A-50)



SELECTOR SW PCB ASSY (A-70/A-50)



PUSH SW PCB A ASSY (A-70/A-50)



PUSH SW PCB BC ASSY (A-70/A-50)



DISPLAY PCB ASSY (A-70/A-50)



HEADPHONE JACK PCB ASSY (A-70/A-50)



NOTES

1. The colors used on the PCB illustrations have the following significance:
   - : +B power supply circuit
   - : −B power supply circuit
   - : GND
   - : Other
2. Resistor values are in ohms (k=1,000 ohms, M=1,000,000 ohms).
3. Capacitor values are in microfarads (p=picofarads).
4. ⚠ Parts marked with this sign are safety critical components. They must always be replaced with identical components - refer to the appropriate parts list and ensure exact replacement.

MAIN PCB ASSY (A-70)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109200	PCB Assy [US]
	5760109210	PCB Assy [C]
	5760109220	PCB Assy [GE, E, UK, A]
	5760111700	PCB [All except C]
	5760118100	PCB [C]
	IC	
IC101	5147064000	NJM4559DD
	TRANSISTORS	
Q1	5230770300	2SC1815Y or GR
Q2	⚠5231755100	2SD880Y
Q3	5232005100	FET 2SK246Y
Q4	5145150000	2SA1015Y or GR
Q5	⚠5760122600	2SB834Y
Q6	5232005100	FET 2SK246Y
Q7~Q9	5230770300	2SC1815Y or GR
Q10	5760121800	2SC1627AY
Q11	⚠5231755100	2SD880Y
Q12	⚠5230770300	2SC1815Y or GR
Q101, Q201	5760102300	FET 2SK170Y
Q102, Q202	5760102300	FET 2SK170Y
Q103, Q203	5145149000	2SA970GR or BL
Q104, Q204	5145149000	2SA970GR or BL
Q105, Q205	5230770300	2SC1815Y or GR
Q106, Q206	5230770300	2SC1815Y or GR
Q107, Q207	5145153000	2SC2240GR or BL
Q108, Q208	5145169000	2SC2235Y
Q109, Q209	5230770300	2SC1815Y or GR
Q110, Q210	⚠5145169000	2SC2235Y
Q111, Q211	⚠5145168000	2SA965Y
Q112, Q212	⚠5145171000	2SD718O
Q113, Q213	⚠5145170000	2SB688O
Q114, Q214	5230770300	2SC1815Y or GR
	DIODES	
D1	5760140400	Zener 05Z-5.6U
D2	5760140200	Zener 05Z-20U
D3	5042220000	1S1555
D4, D5	⚠5224012600	S5277
D6	5760140300	Zener 05Z-13U
D7	5760140500	Zener 05Z-5.1U
D8	⚠5224012600	S5227
D9~D12	⚠5143017000	U05C
D101, D201	5042220000	1S1555
D102, D202	5042220000	1S1555
	RESISTORS	
	All resistors are rated ±5% tolerance, ¼ watt and are carbon type unless otherwise noted.	
R1	5181280000	820Ω
R2	5181304000	8.2kΩ
R3	5181300000	5.6kΩ
R4	⚠5184261000	330Ω Nonflammable
R5	5181284000	1.2kΩ
R6, R7	5181308000	12kΩ
R8	⚠5184261000	330Ω Nonflammable
R9	⚠5181234000	10Ω
R10	⚠5180092000	2.7kΩ ½W
R11	⚠5184249000	100Ω Nonflammable

REF. NO.	PARTS NO.	DESCRIPTION
R12	5181298000	4.7kΩ
R13	5181302000	6.8kΩ
R14	5181322000	47kΩ
R15	5181302000	6.8kΩ
R16	5181348000	560kΩ
R17	5181326000	68kΩ
R18	5181312000	18kΩ
R19	⚠5760141000	820Ω 1W Metal Film
R20	5181296000	3.9kΩ
R21	5181306000	10kΩ
R22	5181294000	3.3kΩ
R23	⚠5760120700	100Ω 3W Cement
R24	5181274000	470Ω
R25	⚠5180092000	2.7kΩ ½W
R26	5181326000	68kΩ
R27	5181314000	22kΩ
R28, R29	5181300000	5.6kΩ
R30, R31	⚠5760141100	3.3kΩ 1W Metal Film
R101, R201	5181258000	100Ω
R102, R202	5181322000	47kΩ
R103, R203	5181242000	22Ω
R104, R204	5181298000	4.7kΩ
R105, R205	5181298000	4.7kΩ
R106, R206	5181272000	390Ω
R107, R207	5181298000	4.7kΩ
R108, R208	5181260000	120Ω
R109, R209	5181234000	10Ω
R110, R210	5181326000	68kΩ
R111, R211	5181300000	5.6kΩ
R112, R212	5181300000	5.6kΩ
R113, R213	5181260000	120Ω
R114, R214	5181276000	560Ω
R115, R215	5181342000	330kΩ
R120, R220	5181282000	1kΩ
R121, R221	5181324000	56kΩ
R122, R222	5181246000	33Ω
R123, R223	5181246000	33Ω
R124, R224	5181306000	10kΩ
R125, R225	5181274000	470Ω
R126, R226	5181270000	330Ω
R127, R227	5181270000	330Ω
R128, R228	5181322000	47kΩ
R129, R229	5181252000	56Ω
R130, R230	5181276000	560Ω
R131, R231	5181306000	10kΩ
R132, R232	5181274000	470Ω
R133, R233	5181258000	100Ω
R134, R234	5181306000	10kΩ
R135, R235	5181308000	12kΩ
R136, R236	5181292000	2.7kΩ
R137, R237	5181260000	120Ω
R138, R238	5181254000	68Ω
R139, R239	5181284000	1.2kΩ
R140, R240	5180088000	1.8kΩ ½W
R141, R241	5180096000	3.9kΩ ½W
R142, R242	5181280000	820Ω
R143, R243	5181280000	820Ω
R144, R244	⚠5184259000	270Ω Nonflammable
R145, R245	⚠5184257000	220Ω Nonflammable
R146, R246	⚠5184257000	220Ω Nonflammable

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

REF. NO.	PARTS NO.	DESCRIPTION
R147, R247	⚠5760120600	0.33Ω×2 5W Cement
R148, R248	5181290000	2.2kΩ
R149, R249	5181310000	15kΩ
R150, R250	⚠5760140900	10Ω 1W Metal Film
R151, R251	5181298000	4.7kΩ
R152, R252	⚠5760140800	6.8Ω 1W Metal Film
	CAPACITORS	
C1	5173395000	Ceramic 0.047μF 50V
C2	5173393000	Ceramic 0.01μF 50V
C3	5172935000	Elec. 100μF 25V
C4	5173393000	Ceramic 0.01μF 50V
C5	5172308000	Ceramic 47pF 50V
C6	5172915000	Elec. 33μF 10V
C7	5172917000	Elec. 33μF 25V
C8	5172935000	Elec. 100μF 25V
C9	5173393000	Ceramic 0.01μF 50V
C10	5172308000	Ceramic 47pF 50V
C11	5172917000	Elec. 33μF 25V
C12	5173393000	Ceramic 0.01μF 50V
C13	5172926000	Elec. 47μF 25V
C14, C15	5173393000	Ceramic 0.01μF 50V
C16	5172946000	Elec. 220μ 50V
C17	5260071400	Elec. 22μF 16V (BP)
C18	5172929000	Elec. 47μF 63V
C19	5172942000	Elec. 220μF 10V
C20	5173006000	Elec. 4.7μF 50V
C21	5172925000	Elec. 47μF 16V
C22, C23	5173393000	Ceramic 0.01μF 50V
C24, C25	5172902000	Elec. 10μF 35V
C26, C27	⚠5760103600	Elec. 4700μF 53V
C28, C29	⚠5760141200	Ceramic 0.01μF 1.4kV
C101, C201	5173390000	Ceramic 0.001μF 50V
C102, C202	5172310000	Ceramic 68pF 50V
C103, C203	5173390000	Ceramic 0.001μF 50V
C104, C204	5172320000	Ceramic 470pF 50V
C105, C205	5172976000	Elec. 2200μF 10V
C106, C206	5054738800	Mylar 0.047μF 50V 5%
C107, C207	5054877800	Mylar 0.01μF 50V 5%
C108, C208	5054881800	Mylar 0.0033μF 50V 5%
C109, C209	5172890000	Elec. 3.3μF 50V
C110, C210	5054813000	Mylar 0.0047μF 50V
C115, C215	5172890000	Elec. 3.3μF 50V
C116, C216	5172310000	Ceramic 68pF 50V
C117, C217	5172320000	Ceramic 470pF 50V
C118, C218	5172942000	Elec. 220μF 10V
C119, C219	5172306000	Ceramic 33pF 50V
C120, C220	5172310000	Ceramic 68pF 50V
C121, C221	5172925000	Elec. 47μF 16V
C122, C222	5172925000	Elec. 47μF 16V
C123, C223	5172313000	Ceramic 120pF 50V
C124, C224	5173400000	Ceramic 5pF 50V
C125, C225	5172935000	Elec. 100μF 25V
C126, C226	5172312000	Ceramic 100pF 50V
C127, C227	5173390000	Ceramic 0.001μF 50V
C128, C228	5172935000	Elec. 100μF 25V
C129, C229	5172320000	Ceramic 470pF 50V
C130, C230	5172320000	Ceramic 470pF 50V
C131, C231	5172308000	Ceramic 47pF 50V
C132, C232	5172308000	Ceramic 47pF 50V

REF. NO.	PARTS NO.	DESCRIPTION
C133, C233	5054827000	Mylar 0.047μF 50V
C134, C234	5054827000	Mylar 0.047μF 50V
	COILS	
L101, L201	5760120900	2.2μH
	FUSES	
F1, F2	⚠5760080700	125V F5A [US, C]
	⚠5142174000	250V F5A [GE, E, UK, A]
	MISCELLANEOUS	
J1	5760142100	Pin Jack, 2P
	5760102200	Heatsink
	5142087000	Holder, Fuse (4 used)
	5760121000	Relay
	5760115500	Pin, Lapping (10 used)
	5760115600	Pin, Lapping; 2P (2 used)
	5760115700	Pin, Lapping; 3P (3 used)
	5760115800	Pin, Lapping; 4P

MAIN PCB ASSY (A-50)

REF. NO.	PARTS NO.	DESCRIPTION
	5760110400	PCB Assy [US]
	5760110410	PCB Assy [C]
	5760110420	PCB Assy [GE, E, UK, A]
	5760111700	PCB [All except C]
	5760118100	PCB [C]
	IC	
IC101	5147064000	NJM4559DD
	TRANSISTORS	
Q1	5145150000	2SA1015Y
Q2	5760121800	2SC1627AY
Q3	5230770300	2SC1815Y
Q4	⚠5231755100	2SD880Y
Q5	5230770300	2SC1815Y
Q101, Q201	5145149000	2SA970GR
Q102, Q202	5145149000	2SA970GR
Q103, Q203	5230770300	2SC1815Y
Q104, Q204	5145167000	2SC2229Y
Q105, Q205	5230770300	2SC1815Y
Q106, Q206	⚠5760121800	2SC1627AY
Q107, Q207	⚠5760121900	2SA817AY
Q108, Q208	⚠5145165000	2SD716O
Q109, Q209	⚠5145172000	2SB686O
	DIODES	
D1, D2	5760140600	Zener 05Z-16U
D3	5760140300	Zener 05Z-13U
D4	5042220000	1S1555
D5	5760140700	Zener 05Z-10U
D6	5042220000	1S1555
D7	⚠5760121700	S5277
D8	5760140300	Zener 05Z-13U
D9	5760140500	Zener 05Z-5.1U
D10	⚠5760121700	S5277
D11~D14	⚠5760121600	1BZ-61

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

REF. NO.	PARTS NO.	DESCRIPTION	
D101, D201	5042220000	1S1555	
	RESISTORS		
	All resistors are rated ±5% tolerance, ¼ watt and are carbon type unless otherwise noted.		
R1, R2	5181288000	1.8kΩ	
R3	5181324000	56kΩ	
R4	5181318000	33kΩ	
R5	5181288000	1.8kΩ	
R6	5181290000	2.2kΩ	
R7	5181326000	68kΩ	
R8	5181338000	220kΩ	
R9	5181332000	120kΩ	
R10	5760141500	1.5kΩ	1W Metal Film
R11	⚠5184249000	100Ω	Nonflammable
R12	5181294000	3.3kΩ	
R13	⚠5760141600	100Ω	3W Cement
R14	5181274000	470Ω	
R15	5181288000	1.8kΩ	
R16	5181326000	68kΩ	
R17	5181314000	22kΩ	
R18	5181300000	5.6kΩ	
R19	5181296000	3.9kΩ	
R101, R201	5181324000	56kΩ	
R102, R202	5181250000	47Ω	
R103, R203	5181280000	820Ω	
R104, R204	5181342000	330kΩ	
R105, R205	5181320000	39kΩ	
R106, R206	5181348000	560kΩ	
R107, R207	5181258000	100Ω	
R108, R208	5181274000	470Ω	
R109, R209	5181322000	47kΩ	
R110, R210	5181282000	1kΩ	
R111, R211	5181324000	56kΩ	
R112, R212	5181306000	10kΩ	
R113, R213	5181246000	33Ω	
R114, R214	5181246000	33Ω	
R115, R215	5181274000	470Ω	
R116, R216	5181270000	330Ω	
R117, R217	5181270000	330Ω	
R118, R218	5181322000	47kΩ	
R119, R219	5181278000	680Ω	
R120, R220	5181304000	8.2kΩ	
R121, R221	5181274000	470Ω	
R122, R222	5181242000	22Ω	
R123, R223	5181282000	1kΩ	
R124, R224	5181294000	3.3kΩ	
R125, R225	5181292000	2.7kΩ	
R126, R226	5181264000	180Ω	
R127, R227	5181254000	68Ω	
R128, R228	5181282000	1kΩ	
R129, R229	⚠5184265000	470Ω	Nonflammable
R130, R230	⚠5184265000	470Ω	Nonflammable
R131, R231	⚠5184257000	220Ω	Nonflammable
R132, R232	⚠5184253000	150Ω	Nonflammable
R133, R233	⚠5184253000	150Ω	Nonflammable
R134, R234	⚠5760141700	0.47Ωx2	3W Cement
R135, R235	⚠5760140900	10Ω	1W Metal Film

REF. NO.	PARTS NO.	DESCRIPTION		
	CAPACITORS			
C1	5173395000	Ceramic	0.047μF	50V
C2, C3	5173393000	Ceramic	0.01μF	50V
C4, C5	5172944000	Elec.	220μF	25V
C6	5173393000	Ceramic	0.01μV	50V
C7, C8	5172902000	Elec.	10μF	35V
C9	5172927000	Elec.	47μF	35V
C10	5172935000	Elec.	100μF	25V
C11	5172928000	Elec.	47μF	50V
C12	5172946000	Elec.	220μF	50V
C13	5173393000	Ceramic	0.01μF	50V
C14	5172925000	Elec.	47μF	16V
C15	5173393000	Ceramic	0.01μF	50V
C16, C17	5172902000	Elec.	10μF	35V
C18, C19	⚠5760128800	Elec.	3300μF	50V
C20, C21	⚠5760141200	Ceramic	0.01μF	1.4kV
C101, C201	5172890000	Elec.	3.3μF	50V
C102, C202	5172908000	Elec.	22μF	16V
C103, C203	5054888800	Mylar	0.0018μF	50V 5%
C104, C204	5054892800	Mylar	0.0056μF	50V 5%
C105, C205	5054896800	Mylar	0.0015μF	50V 5%
C106, C206	5054876800	Mylar	0.0022μF	50V 5%
C107, C207	5172882000	Elec.	1μF	50V
C108, C208	5172882000	Elec.	1μF	50V
C109, C209	5172310000	Ceramic	68pF	50V
C110, C210	5173393000	Ceramic	0.01μF	50V
C111, C211	5172320000	Ceramic	470pF	50V
C112, C212	5172907000	Elec.	220μF	10V
C113, C213	5172924000	Elec.	47μF	10V
C114, C214	5172924000	Elec.	47μF	10V
C115, C215	5172306000	Ceramic	33pF	50V
C116, C216	5172306000	Ceramic	33pF	50V
C117, C217	5172926000	Elec.	47μF	25V
C118, C218	5173400000	Ceramic	5pF	50V
C119, C219	5172313000	Ceramic	120pF	50V
C120, C220	5173390000	Ceramic	0.001μF	50V
C121, C221	5172320000	Ceramic	470pF	50V
C122, C222	5172320000	Ceramic	470pF	50V
C123, c223	5172308000	Ceramic	47pF	50V
C124, C224	5172308000	Ceramic	47pF	50V
C125, C225	5054827000	Mylar	0.047μF	50V
	FUSES			
F1, F2	⚠5760100400	125V	F4A [US, C]	
	⚠5041156000	250V	F4A [GE, E, UK, A]	
F101, F201	⚠5760100400	125V	F4A [US, C]	
	⚠5041156000	250V	F4A [GE, E, UK, A]	
	MISCELLANEOUS			
J1	5760142100	Pin Jack, 2P		
	5760102200	Heatsink		
	5142087000	Holder, Fuse (8 used)		
	5760115500	Pin, Lapping (9 used)		
	5760115600	Pin, Lapping; 2P		
	5760115700	Pin, Lapping; 3P (3 used)		
	5760115800	Pin, Lapping; 4P		

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

SELECTOR SW PCB ASSY (A-70/A-50)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109300	PCB Assy [All except C]
	5760109310	PCB Assy [C]
	5760110900	PCB [All except C]
	5760110500	PCB [C]
CARBON RESISTORS (All resistors are rated ±5% tolerance and ¼ watt.)		
R40~R42	5240168600	1.5kΩ
R160, R260	5240174600	470kΩ
R161	5240170000	5.6kΩ
R261	5181300000	5.6kΩ
R162	5240171200	18kΩ
R262	5181312000	18kΩ
R163, R263	5240168600	1.5kΩ
R164, R264	5240170200	6.8kΩ
R165	5240174600	470kΩ
R265	5181346000	470kΩ
R166	5240171200	18kΩ
R266	5181312000	18kΩ
R167, R267	5240169400	3.3kΩ
CAPACITORS		
C35	5173395000	Ceramic 0.047μF 50V
C150, C250	5054845000	Mylar 0.0022μF 50V
C151, C251	5054855000	Mylar 0.018μF 50V
C152, C252	5054862000	Mylar 0.012μF 50V
C153, C253	5054854000	Mylar 0.068μF 50V
VARIABLE RESISTORS		
VR1, VR2	5760121100	100kΩ(C)x2
MISCELLANEOUS		
SW1	5760118300	Push Switch, 3-gang
SW2	5760118400	Push Switch, 2-gang
	5760115600	Pin, Lapping; 2P
	5760115900	Pin, Lapping; 6P
	6760116000	Pin, Lapping; 9P

PUSH SW PCB A ASSY (A-70)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109700	PCB A Assy [All except C]
	5760109710	PCB A Assy [C]
	5760111300	PCB A [All except C]
	5760118700	PCB A [C]
CARBON RESISTORS (All resistors are rated ±5% tolerance and ¼ watt.)		
R183, R283	5240168200	1kΩ
R184, R284	5240172400	56kΩ
R185, R285	5240171200	18kΩ
R186, R286	5240175400	1MΩ
R187, R287	5240175400	1MΩ
CAPACITORS		
C160, C260	5172318000	Ceramic 250pF 50V
C161, C261	5054824000	Mylar 0.033μF 50V
C162, C262	5054802000	Mylar 0.01μF 50V
C163, C263	5054665000	Tant. 0.15μF 35V
VARIABLE RESISTOR		
VR3	5760121200	250kΩ(B)x2, 500kΩ(W)
MISCELLANEOUS		
SW4	5760119000	Push Switch, 5-gang
	5760115900	Pin, Lapping; 6P

PUSH SW PCB A ASSY (A-50)

REF. NO.	PARTS NO.	DESCRIPTION
	5760110600	PCB A Assy [All except C]
	5760110610	PCB A Assy [C]
	5760111300	PCB A [All except C]
	5760118700	PCB A [C]
CARBON RESISTORS (All resistors are rated ±5% tolerance and ¼ watt.)		
R183, R283	5240168200	1kΩ
R184, R284	5240172400	56kΩ
R185, R285	5240171200	18kΩ
R186, R286	5240175400	1MΩ
R187, R287	5240175400	1MΩ
CAPACITORS		
C160, C260	5172317000	Ceramic 250pF 50V
C161, C261	5054824000	Mylar 0.033μF 50V
C162, C262	5054802000	Mylar 0.01μF 50V
C163, C263	5054665000	Tant. 0.15μF 35V
VARIABLE RESISTOR		
VR3	5760121200	250kΩ(B)x2, 500kΩ(W)
MISCELLANEOUS		
SW4	5760119100	Push Switch, 4-gang

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

PUSH SW PCB BC ASSY (A-70/A-50)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109800	PCB B C Assy [All except C]
	5760109810	PCB BC Assy [C]
	5760111400	PCB B [All except C]
	5760119200	PCB B [C]
	5760111500	PCB C [All except C]
	5760119300	PCB C [C]
	CARBON RESISTORS	
C180, C280	5240172600	68kΩ ¼W 5%
C181, C281	5240170400	8.2kΩ ¼W 5%
C182, C282	5240168200	1kΩ ¼W 5%
	CAPACITOR	
C40	5173395000	Ceramic 0.047μF 50V
	MISCELLANEOUS	
SW3	5760119500	Push Switch, 5-gang
	5760119400	Pin, Lapping; 15P

DISPLAY PCB ASSY (A-70/A-50)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109900	PCB Assy [All except C]
	5760109910	PCB Assy [C]
	5760111600	PCB [All except C]
	5760119600	PCB [C]
	IC	
IC102	5760121300	LT-1048
	DIODES	
D110, D210	5042213000	1N60
D111, D211	5042220000	1S1555
	CARBON RESISTORS	
	All resistors are rated ±5% tolerance and ¼ watt.	
R50	5181316000	27kΩ
R51	5181288000	1.8kΩ
R190, R290	5181308000	12kΩ
R191, R291	5181286000	1.5kΩ
R192, R292	5181318000	33kΩ
R193, R293	5181324000	56kΩ
	CAPACITORS	
C170, C270	5172896000	Elec. 4.7μF 50V
	VARIABLE RESISTOR	
VR4	5280003302	Semi-fixed, 5kΩ(B)

HEADPHONE JACK PCB ASSY (A-70/A-50)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109500	PCB Assy [All except C]
	5760109510	PCB Assy [C]
	5760111100	PCB [All except C]
	5760118500	PCB [C]
	RESISTORS	
R168, R268	5760141400	330Ω 1W 5% Metal Film
J4	5760141300	Jack, PHONES

SP TERMINAL PCB ASSY (A-70/A-50) (PC Board omitted)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109400	PCB Assy [All except C]
	5760109410	PCB Assy [C]
	5760111000	PCB [All except C]
	5760118200	PCB [C]
J5	5760102700	Terminal, Push; 8P

LED PCB ASSY (A-70/A-50) (PC Board omitted)

REF. NO.	PARTS NO.	DESCRIPTION
	5760109600	PCB Assy [All except C]
	5760109610	PCB Assy [C]
	5760111200	PCB [All except C]
	5760118600	PCB [C]
D20~D22	5760112400	LED PR5531K
	5760109100	Holder, LED; D

[US]: U.S.A. [C]: CANADA [GE]: GENERAL EXPORT [E]: EUROPE [UK]: U.K. [A]: AUSTRALIA

SEMICONDUCTOR ELECTRODES

NJM4559DD
(TOP VIEW)



2SA817AY
2SA965Y



2SA970GR
2SA1015Y



2SB686O
2SB688O



2SB834Y



2SC1627AY
2SC2229Y
2SC2235Y



2SC1815Y
2SC2240GR



2SD716O
2SD718O



2SD880Y



2SK170Y
2SK246Y



05Z5.1U
05Z5.6U
05Z10U
05Z13U
05Z16U
05Z20U



1BZ-61



1N60



1S1555



S5277



U05C



PR5531K



TEAC SCHEMATIC DIAGRAM A-50



NOTES

1. All resistors are 1/4W, ±5%, unless otherw
   Resistor values are in ohms (k=kilo-ohms,
2. All capacitor values are in microfara
3. 0 dB=1 V
4. The DC voltages given in each portion
   measured under no-signal conditions.
5. ⚠ Parts marked with this sign are safety c
   They must always be replaced with ide
   refer to the appropriate parts list and e
   ment.
6. ——— : +B power supply
7. ——— : −B power supply
8. ⟿ : Audio signal path (shown for L c
9. [ ] : Front panel indication
10. [ ] : Rear panel indication

A-70 DC Integrated Stereo Amplifier













NOTES

1. All resistors are 1/4W, ±5%, unless otherwise noted. Resistor values are in ohms (k=kilo-ohms, M=mega-ohms).
2. All capacitor values are in microfarads (p=pico-farads).
3. 0 dB=1 V
4. The DC voltages given in each portion are reference values measured under no-signal conditions.
5. ⚠ Parts marked with this sign are safety critical components. They must always be replaced with identical components - refer to the appropriate parts list and ensure exact replacement.
6. ——— : +B power supply
7. ——— : −B power supply
8. ~~~~ : Audio signal path (shown for L ch only)
9. [ ] : Front panel indication
10. [ ] : Rear panel indication

A-50 DC Integrated Stereo Amplifier

TEAC SCHEMATIC DIAGRAM A-70



NOTES

1. All resistors are 1/4W, ±5%, unle
   Resiston values are in ohms (k=k
2. All capacitor values are in
3. 0 dB=1 V
4. The DC voltages given in each
   measured under no signal condit
5. ⚠ Parts marked with this sign ar
   They must always be replaced
   refer to the appropriate parts
   ment.
6. ——— : +B power supply
7. ——— : -B power supply
8. ▶ : Audio signal path (show
9. [ ] : Front panel indication
10. [ ] : Rear panel indication



NOTES

1. All resistors are 1/4W, ±5%, unless otherwise noted.
2. Resistor values are in ohms (k=kilo-ohms, M=mega-ohms).
3. All capacitor values are in microfarads (p=pico-farads).
4. 0 dB=1 V
5. The DC voltages given in each portion are reference values measured under no-signal conditions.
6. ⚠ Parts marked with this sign are safety critical components. They must always be replaced with identical components - refer to the appropriate parts list and ensure exact replacement.

——— : +B power supply
——— : −B power supply
——— : Audio signal path (shown for L ch only)
[Front] : Front panel indication
[Rear] : Rear panel indication

A-70 DC Integrated Stereo Amplifier